

SP00735 (Special Provisions for the 2021 Book) (Bidding on or after: ~~0910-01-231~~
Last updated: ~~056-1621-231~~
This Section requires SP00730
*This Section require SP00705 when
emulsified asphalt fog coat is required.
Requires SP00710 or SP00715 when
chip seal is required.)*

SECTION 00735 - EMULSIFIED ASPHALT CONCRETE PAVEMENT

(Follow all instructions and make all edits with “Track Changes” turned on. If there are no instructions [orange text] above a subsection, paragraph, sentence, or bullet, then include it in the project. Delete all orange text before preparing the final document. All other modifications to this Section will require ODOT Technical Resource and State Specifications Engineer approval.)

Comply with Section 00735 of the Standard Specifications modified as follows:

00735.11 Emulsified Asphalt - In the paragraph that begins "Obtain Emulsified Asphalt samples according to AASHTO T 40..." replace the words "AASHTO T 40" with the words "AASHTO R 66".

00735.42 Preparation of Underlying Surfaces – Add the following paragraph to the end of this subsection:

Remove existing pavement markers, recessed markers, and pavement legends before paving. Remove pavement lines, bars, and pavement legends as shown or directed and according to 00225.45.

(Use the following subsection .45(b) on projects that allow alternate methods of depositing EAC on the road. Obtain the methods from the Designer.)

00735.45(b) Depositing - Add the following to the end of this subsection:

The following alternate methods of depositing EAC may be used:

-

00735.48(b) Drop-Offs - Replace the bullet that begins "Provide warning signs and markings..." with the following bullet:

- Provide warning signs and markings according to Sections 00221, 00222, 00224 and 00225 where abrupt or sloped edge drop-offs greater than 1 inch in height occur.